



## 4 ZONES INDUCTION BOILING TOP

---

616112 - PIN70E7N

---

## SPECIFICATIONS

Tecno70 is a complete, practical, compact and functional range. This range offers a winning price/quality ratio ideal for restaurants, cafés and small canteens.

The 35/70/105 cm wide units make effective use of space, offering professional performance.

### COMPACT

The units are compact, meaning you can work with professional equipment in small spaces.

### COMPREHENSIVE AND FLEXIBLE

The range is made up of dozens of top and freestanding units which can easily be combined with different compartments and oven and refrigerated base units to meet your every cooking need!

### SAFETY

The gas appliances are certified by German body DVGW and have passed the most stringent safety tests. The electrical appliances are tested at our facility and are CE certified

### ULTRA-RELIABLE

Created in 2001, the range has been progressively enhanced and expanded, reaching a very high level of satisfaction among users and installers.

### FINISHES

Design features such as moulded tops with rounded corners, removable splashback and joining elements to make cleaning easier and ensure good hygiene.

### TECHNICAL COMPARTMENT

The majority of the units are fitted with a technical compartment at the back for connections and hook-ups.

## INDUCTION COOK TOPS

- The most innovative technology in horizontal cooking.
- All tops have 2 or 4 heating zones with 1 or 2 independently controlled generators respectively.
- Energy savings: in operation only when pans are detected.
- Minimum heat dispersion.
- Easy to clean.
- Installable on neutral elements, with doors and/or drawers and on refrigerated base units.

## TECHNICAL DATA

Total Power	<b>14 kW</b>	Width	<b>70 cm</b>
EL Power	<b>14 kW</b>	Depth	<b>70 cm</b>
Frequency	<b>50/60 Hz</b>	Height	<b>28 cm</b>
Voltage	<b>400 3 ~ V</b>	Packaging Width	<b>77,0 cm</b>
Cooking Zones Power	<b>4x3,5 n°- kW</b>	Packaging Depth	<b>81,0 cm</b>
Number of Cooking zones	<b>4 n°</b>	Packaging Height	<b>53,0 cm</b>
Foot high	<b>15 mm</b>	Net Weight	<b>44 kg</b>
Foot adjustment	<b>15/25 mm</b>	Gross Weight	<b>51,4 kg</b>
IPX	<b>3</b>	Volume	<b>0,3300 m<sup>3</sup></b>

## ACCESSORIES

- 220585: JOINT ELEMENT